



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN2036REV
Address	Low Road, Low Street, Wortwell, Harleston, 627690, 284821
Area	0.5ha
Current land use	Greenfield
Proposed land use	Residential
Internal Drainage District (IDD)	Waveney, Lower Yare and Lothingland IDD

Location of the site within the catchment

The site is located in the River Waveney Catchment, between the main Waveney River and the Starston Brook tributary. The River Waveney flows from its source in the Regrave and Lopham Fen National Nature Reserve, through the towns of Harleston, Diss, Bungay and Beccles, and joins the River Yare before it reaches the sea at Great Yarmouth. The Starston Brook flows from its source near Sneath Common, through Starston and Redenhall, before joining the River Waveney near Fixton Road.

Existing drainage features

The site is located approximately 0.45km away from the Starston Brook tributary in the north-west. The Environment Agency states that the waterbody is natural, having not been subject to any modifications. Approximately 0.47km south-east from the site is the River Waveney. This section of the river is heavily modified, having been subject to channel straightening and deepening over the years. Online imagery suggests there are also a number of drainage ditches in the area, as well as a cluster of lakes behind the site that surround a Caravan Park. Apart from those specified, there are no additional watercourses within or near the site.

Fluvial

The proportion of site at risk:

FZ3b – 0.0%
FZ3a – 0.3%
FZ2 – 7.3%
FZ1 – 92.7%

The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).

Available data:

The Environment Agency's 2022 hydraulic model for the River Waveney has been used for this assessment.

Flood characteristics:

The site is only shown to be impacted by fluvial flooding in the south. The modelling shows the site is not at risk during the 3.3% AEP event. In the 1% AEP event the flood extent impacts Low Road to the west of the site and encroaches slightly into the southwest corner of the site. Maximum depths on the site are 0.05m, with velocities of up to 0.001m/s and a hazard classification of 'Very low hazard'.

	In the 0.1% AEP event the flood extent encroaches into the south of the site. Maximum flood depths on the site reach 0.12m, with velocities of up to 0.004m/s and a hazard classification of 'Very low hazard'.
Coastal and Tidal	The site is not at risk from tidal or coastal flooding.
Surface Water	<p>Proportion of site at risk (RoFFSW): 3.3% AEP – 0% 1% AEP – 0% 0.1% AEP – 0%</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %)</i></p> <p>Description of surface water flow paths: There is no risk of surface water flooding within the site in all modelled AEP events. The surrounding roads are shown to be impacted by surface water in all modelled flood events, which is discussed within the access and egress section.</p>
Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding dataset, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The entire site is shown to have less than a 25% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater Map emulates this along the western half of the site where it is designated as 'No risk'. This means that there is a negligible risk from groundwater flooding due to the nature of the local geological deposits. However, along the eastern part of the site groundwater levels are predicted to be at or very near (within 0.025m) of the ground surface. This means that is a risk of groundwater flooding to both surface and subsurface assets. Groundwater may emerge at significant rates and has the capacity to flow overland and/or pond within any topographic low spots.</p> <p>Any groundwater emerging in the eastern part of the site will likely follow the topography draining in an easterly direction away from the site.</p> <p>This assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage</p>
Sewers	The site is located in a postcode (IP20 0) with 15 recorded historic sewer flooding incidences between May 2013 and March 2024 according to information provided by Anglian Water.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	This site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	The north-east and south-east corners of the site are included in the River Waveney from Diss to Bungay Flood Alert Area.
Access and egress	<p>The site is currently accessible from High Road which runs to the north of the site and then Low Road which runs along the western site boundary.</p> <p>Access and egress to the site from the west via High Road and Low Road is shown to be unaffected in all modelled fluvial flooding events, considering climate change.</p> <p>There is surface water flooding to the surrounding roads in all modelled surface water events.</p>

	<p>In the 3.3% AEP event, there is minimal flooding on High Road, adjacent to the site, and along Low Road nearby. The estimated depth of this road flooding is less than 0.30m. Access to and from the site will therefore be maintained.</p> <p>In the 1% AEP event, the surface water flooding extent is slightly greater than in the 3.3% AEP event along High Road and Low Road. The estimated depth of this flooding is less than 0.30m. Access to and from the site will therefore be maintained.</p> <p>In the 0.1% AEP event, the surface water flooding extents increase along High and Low Road. However, depths are still shown to remain below 0.3m, with maximum velocities of between 1 and 2m/s. Therefore, access and egress to the site for emergency vehicles is likely to still be possible.</p> <p>Safe access and egress will need to be demonstrated in the 1% AEP plus climate change surface water event. Site drainage proposals should address the requirements for access routes, avoid impeding surface water flows and preserve the storage of surface water to avoid exacerbation of flood risk in the wider catchment.</p>
--	--

Dry Islands	The site is not located on a dry island.
--------------------	--

Climate change

Implications for the site	<ul style="list-style-type: none"> • Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of surface water flooding. • The fluvial 1% AEP and 0.1% AEP extents plus a 25% allowance for climate change were made available for the River Waveney for this assessment. • The site is shown to be sensitive to increased fluvial flood risk due to climate change. Within the 0.1% AEP plus 25% event the flood extent in the south of the site increases, and the flood extent also starts to slightly encroach in the northeast corner of the site. • Climate change should also be considered for surface water events; at the site-specific stage, the 1% AEP +40% event is considered as part of surface water drainage strategies, or surface water modelling. The 1% AEP +40% event mapping suggests that the site is unlikely to be at increased risk of surface water flooding in future. In addition to the SuDS features designed to accommodate runoff from new development infrastructure the proposals should also address the potential loss of natural storage of rainfall and runoff provided by the land in its natural condition. • Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
----------------------------------	--

Requirements for drainage control and impact mitigation
--

Broad-scale assessment of possible SuDS	<p>Geology & Soils</p> <ul style="list-style-type: none"> • Geology at the site consists of: <ul style="list-style-type: none"> ○ Bedrock – Neogene and Quaternary (undifferentiated) Formation, made from conglomerates, gravel, silt, sand and muddy aeolian loess-type deposits. ○ Superficial – River Terrace Deposits- Sand and Gravel • Soils at the site consist of lime-rich loamy and clayey soils – high fertility, impeded drainage. <p>SuDS</p> <ul style="list-style-type: none"> • Groundwater levels in the east side of the site are indicated to be at or very near (within 0.025m) ground level and there is a risk of groundwater flooding at the surface during a 1% AEP event, which may flow to and pool within topographic low spots. Detention and attenuation features should be designed to prevent groundwater ingress from impacting hydraulic capacity and structural integrity. Additional site investigation work may be required to support the detailed design of the drainage system. This may include groundwater monitoring to demonstrate that a sufficient unsaturated zone has been provided above the highest occurring groundwater level. Below ground development such as basements are not appropriate at this site. • BGS data indicates that the underlying geology is a combination of conglomerates, gravel, silt, sand and muds which are likely to be with highly variable permeability. This should be confirmed through infiltration testing. Off-site discharge in
--	---

	<p>accordance with the SuDS hierarchy may be required to discharge surface water runoff from the site.</p> <ul style="list-style-type: none"> • The site is not located within a Groundwater Source Protection Zone and there are no restrictions over the use of infiltration techniques with regard to groundwater quality. • The site is not located within a historic landfill site. • Any surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques. • The site is within the Waveney, Lower Yare and Lothingland Internal Drainage Board district who may have additional requirements regarding discharge rates (directly or indirectly) into their district. There is a Board maintained watercourse located to the east of the site. The IDB should be consulted during the detailed design of the site to establish the Board's requirements and determine whether there will be a need to apply for surface water discharge or ordinary watercourse consents. Further information is provided in the Level 2 SFRA Report. • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.
<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints. • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies. • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.
<p>NPPF and planning implications</p>	
<p>Exception Test requirements</p>	<p>The Local Authority will need to confirm that the Sequential Test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied. The NPPF classifies residential development as 'More Vulnerable'.</p> <p>As part of the site is in Flood Zone 3a, the Exception Test is required for the site.</p>
<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site is at fluvial flood risk. • All sources of flooding should be considered as part of a site-specific flood risk assessment. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich City Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority, Lead Local Flood Authority and the Environment Agency should be undertaken at an early stage.

- The development should be designed with mitigation measures in place where required.

Guidance for site design and making development safe:

- The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF’s policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG).
- Safe access and egress will need to be demonstrated in the 1% AEP plus climate change fluvial and rainfall events, using the depth, velocity and hazard outputs. Ideally, the access route should be situated 300mm above the designed flood level and waterproofing techniques should be used where necessary. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk.
- Resilience measures will be required if buildings are situated in flood risk areas.
- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.
- Areas at risk from surface water flooding should ideally be integrated into green infrastructure, which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. Integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and to ensure that overland flows do not overwhelm future sustainable drainage features.
- The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA, IDB or Anglian Water).

Key messages

Development at the site is likely to be able to proceed if:

- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with habitable floor levels above the fluvial design flood event (1% AEP) taking into account climate change.
- If flood mitigation measures are implemented then they are tested to ensure that they will not displace water elsewhere (for example, if land is raised to permit development on one area, compensatory flood storage will be required in another).
- Space for surface water to be stored on the site is provided and rainwater harvesting should be considered.
- The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA, IDB or Anglian Water).

Mapping Information

The key dataset used to make planning recommendations regarding this site were the Environment Agency’s detailed 2022 hydraulic model for the River Waveney.

Flood Zones	Flood Zones 2, 3a and 3b have been taken from the Environment Agency’s detailed 2022 hydraulic model for the River Waveney.
Climate change	Climate change allowances for the 1% AEP and 0.1% AEP events with a 25% uplift were used for assessing fluvial impacts of climate change on the River Waveney. For surface water a 1% AEP plus 40% scenario has been considered.
Fluvial depth, velocity and hazard mapping	Fluvial depth, velocity and hazard mapping was available from the Environment Agency’s detailed 2022 hydraulic model for the River Waveney.

Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, velocity, and hazard mapping is taken Environment Agency's Risk of Flooding from Surface Water mapping.



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN0274REVA
Address	The Street, Gillingham, South Norfolk, 40862 91986
Area	1.24ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment
The site is located in the River Waveney Catchment, between Ellingham Mill and Burgh St.Peter. The River Waveney flows from its source in the Regrave and Lopham Fen National Nature Reserve, through the towns of Harleston, Diss, Bungay and Beccles, and joins the River Yare before it reaches the sea at Great Yarmouth.

Existing drainage features
The site is located approximately 0.9km north-east of the River Waveney. The Environment Agency states that the reach section in which the site is located near is heavily modified, having undergone channel straightening and deepening over the years. Online imagery suggests there are drainage ditches behind the site that direct water to the main river channel. Apart from those specified, there are no additional watercourses within the site boundary or near the site.

Fluvial

The proportion of site at risk (Environment Agency's Flood Map for Planning):
FZ3 – 59%
FZ2 – 85%
FZ1 – 15%

The proportion of site at risk (Gillingham Strategic Model – fluvial only):
1% AEP - 2%
0.1% AEP - 2%

The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).

Available data:
High level 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model).
The updated PPG defines the functional floodplain as land which would flood in the 3.3% AEP extent. As this was not available for the Gillingham Strategic model, Flood Zone 3a can be used as a conservative indication.

Flood characteristics:
The modelled fluvial scenarios show very limited fluvial flood risk to the site. Flood water flows along The Street adjacent the southern border of the site, crossing slightly into the site.

	<p>In the 1% AEP event, the maximum flood depths along the site boundary reach 0.75m, with velocities of up to 2.3m/s and a maximum hazard classification of 'Danger for all'. In the 0.1% AEP event, there are minimal changes to the depths and velocities along this flow path.</p>
<p>Coastal and Tidal</p>	<p>The proportion of site at risk (Gillingham Strategic Model – tidal only): 1% AEP - 0% 0.5% AEP - 40% 0.1% AEP – 52%</p> <p>Available data: High level 2D tidal modelling was undertaken in TUFLOW based on the application of water levels from Coastal Flood Boundary (CFB) Extreme Sea Levels dataset.</p> <p>Flood characteristics: The eastern half of the site is shown to be at considerable tidal risk in both the 0.5% and 0.1% AEP events. The tidal extent increases by about 15m into the site between the 0.5% and 0.1% AEP events. In the 0.5% AEP event the maximum depths across the site reach a maximum of 1.7m, with velocities of up to 0.81m/s and a maximum hazard classification of 'Danger for most'. In the 0.1% AEP event the maximum depths increase across the site up to 2.1m, with velocities of up to 0.89m/s and a maximum hazard classification of 'Danger for all'.</p>
<p>Surface Water</p>	<p>Proportion of site at risk (RoFfSW): 3.3% AEP – 7% Max depth 0.3 – 0.60m Max velocity 0.5– 1.0m/s 1% AEP – 10% Max depth 0.3 – 0.6m Max velocity 0.50 – 1.00m/s 0.1% AEP – 18% Max depth 0.6 – 0.9m Max velocity 0.5 – 1.00m/s <i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %)</i></p> <p>Description of surface water flow paths: The site is predicted to be affected by surface water in all modelled scenarios. In the 3.3% surface water event, surface water ponds in the topographic depression in the southern corner of the site. Flood depths are largely below 0.3m, deeper in the centre of the ponding. Velocities remain largely below 0.25m/s with isolated areas where velocities reach up to between 0.5 and 1.0m/s. Hazard across most of the flooded area is classified as 'Very low hazard'.</p> <p>In the 1% AEP event the area of predicted flooding expands, and feeds into a surface water flow along The Street. A small surface water flow also forms in the east of the site, toward the area of ponding. Flood depths are between 0.3 and 0.6m in the centre of the ponding and below 0.3m across the rest of the flooded area. Velocities are mostly below 0.25m/s with small areas where velocities reach up to between 0.5 and 1.0m/s. The hazard is classified as 'Danger for some' across most of the flooded area, rising to 'Danger for most' in the flow along the southern border.</p> <p>In the 0.1% AEP event, a predicted surface water flow covers the east of the sites, flowing from the north-east corner to the southern corner, joining the flow path along The Street. Depths are greatest in the south corner, reaching between 0.6 and 0.9m adjacent The Street and between 0.3 and 0.6m across the rest of the southern corner. The rest of the flooded area has depths below 0.3m. Velocities are greatest in the centre of the flow, between 0.5 and 1.0m/s. The hazard is greatest in the southern corner with a classification of 'Danger for most' and a rating of 'Very low hazard' across the rest of the flooded area.</p>

Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The following comments can be made about groundwater flood risk:</p> <ul style="list-style-type: none"> • The northernmost part of the site has less than a 25% susceptibility to groundwater flood emergence. • The remainder of the site has between a 25% and 50% susceptibility to groundwater flood emergence. <p>The JBA Groundwater Emergence Map shows large parts of the site are classified as 'No risk'. This means that there is a negligible risk from groundwater flooding due to the nature of the local geological deposits. However, part of the northeast of the site is predicted to have groundwater levels between 0.025m and 0.5m below the ground surface. Any groundwater emerging in this area is likely to follow the topography draining in a south-easterly direction impacting the southeast corner of the site.</p> <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located in a postcode (NR34 0) with 15 recorded historic sewer flooding incidences between May 2013 and March 2024 according to information provided by Anglian Water.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	This site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Alert or Flood Warning Area.
Access and egress	<p>The site is accessed via The Street which runs along the south-western border of the site. The Street can be accessed through Gillingham to the east or along Old Yarmouth Road and Geldeston Road from the west.</p> <p>Whilst The Street is not at significant risk from surface water where it runs adjacent to the site, there is surface water flood risk along The Street to the south of the site. Old Yarmouth Road and Geldeston Road are shown to be significantly impacted by a large surface water flow path in all modelled surface water events.</p> <p>In all modelled fluvial events, there is considerable flood risk across Geldeston Road and Yarmouth Road. There is also a flow path which forms along the site boundary adjacent to The Street, with flood depths of up to 0.75m and a hazard classification of 'Danger for all' within the 1% and 0.1% AEP events. Therefore access and egress to the site is likely to be impacted.</p> <p>Safe access and egress will need to be demonstrated in the 1% AEP plus climate change surface water event and fluvial events and the 0.5% AEP plus climate change tidal event. Ideally, the access route should be situated 300mm above the designed flood level and waterproofing techniques should be used where necessary. Raising of access routes must not impact on surface water flow routes.</p> <p>Consideration should be given to the siting of access points with respect to areas of flood risk. A Flood Warning and Evacuation plan should be in place for the site. Alternatively, risk could be managed by inclusion of a higher refuge and a flood response plan that meets the requirements of the Local Council and their Emergency Planner, considering the likely warning time and duration of flooding.</p>
Dry Islands	The site is not located on a dry island.
Climate change	

Implications for the site

- Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding.
- The central and higher climate change scenarios have been modelled as part of this assessment. Modelling suggests that the site will not be at significantly greater fluvial risk in the future, even during the 0.1% AEP event in the higher central scenario, although the flooding on The Street will increase in depth and velocity.
- In terms of tidal risk, the site is shown to be highly sensitive to the impacts of climate change. Between the 0.5% AEP present day and 0.5% AEP 2122 higher central climate change events, there is a considerable increase in flood extent across the site and maximum depths on the site increase from 1.7m up to 2.8m.
- Climate change should also be considered for surface water events; at the site-specific stage, the 1% AEP +40% event is considered as part of surface water drainage strategies, or surface water modelling. The 1% AEP +40% event mapping suggests that the site is unlikely to be at increased risk of surface water flooding in future, although there remains a significant risk to the area around the site. In addition to the SuDS features designed to accommodate runoff from new development infrastructure the proposals should also address the potential loss of natural storage of rainfall and runoff provided by the land in its natural condition.

Requirements for drainage control and impact mitigation

Broad-scale assessment of possible SuDS

Geology & Soils

- Geology at the site consists of:
 - Bedrock- Crag Group-Sand.
 - Superficial- Lowestoft Formation- Diamicton and Lowestoft Formation-Sand and Gravel.
- Soils at the site consist of:
 - Slowly permeable seasonally wet slightly acid but base-rich loamy and clayey soils

SuDS

- Groundwater levels are indicated to be less than 0.5m below ground level during a 1% AEP event in parts of the northeast of the site. Detention and attenuation features should be designed to prevent groundwater ingress from impacting hydraulic capacity and structural integrity. Additional site investigation work may be required to support the detailed design of the drainage system. This may include groundwater monitoring to demonstrate that a sufficient unsaturated zone has been provided above the highest occurring groundwater level. Below ground development such as basements are not appropriate at this site.
- BGS data indicates that the underlying geology is sand which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy.
- The site is not located within a historic landfill site.
- The entire site is located within a Groundwater Source Protection Zone 3. Infiltration techniques may not be suitable and should only be used following the granting of any required environmental permits from the Environment Agency for Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints.
- Proposed attenuation features such as basins, ponds and tanks should be located outside of Flood Zone 3 to avoid the potential risks to the hydraulic capacity or structural integrity of these features. Surface water outfalls that discharge into the River Waveney may be susceptible to surcharging due to water levels in the River Waveney. The impacts of flood flows will need to be considered in terms of the attenuation storage requirements of the site and placement of the outfalls.
- Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques.
- The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 3.3%, 1% and 0.1% AEP events. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space.

	<ul style="list-style-type: none"> • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.
<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints. • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies. • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.
<p>NPPF and planning implications</p>	
<p>Exception Test requirements</p>	<p>The Local Authority will need to confirm that the sequential test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied.</p> <p>The NPPF classifies residential development as 'More Vulnerable'. As part of the site is in Flood Zone 3a, the Exception Test is required for the site.</p>
<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site is in Flood Zone 3a. • All sources of flooding, particularly the risk of fluvial, tidal, and surface water should be considered as part of a site-specific flood risk assessment. Detailed modelling should be undertaken to confirm the likely impact of fluvial and tidal flooding on the site both in the present-day and future. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich City Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority, Lead Local Flood Authority and the Environment Agency should be undertaken at an early stage. • The development should be designed to ensure that mitigation measures are in place to ensure the development does not flood, or that ground level space is used for less vulnerable parts of the development. <p>Guidance for site design and making development safe:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site is in Flood Zone 3a. • All sources of flooding, particularly the risk of fluvial, tidal, and surface water should be considered as part of a site-specific flood risk assessment. Detailed modelling should be undertaken to confirm the likely impact of fluvial and tidal flooding on the site both in the present-day and future. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich

	<p>City Council’s Local Plan policies, and the Norfolk County Council Lead Local Flood Authority’s Statutory Consultee for Planning Guidance Document.</p> <ul style="list-style-type: none"> • Consultation with the Local Authority, Lead Local Flood Authority and the Environment Agency should be undertaken at an early stage. • The development should be designed to ensure that mitigation measures are in place to ensure the development does not flood, or that ground level space is used for less vulnerable parts of the development.
--	--

Key messages

The site is currently shown to be at considerable tidal flood risk both in the present day and in the future considering climate change. Development may be able to proceed if:

- Detailed modelling undertaken as part of the site-specific flood risk assessment demonstrates that the site is not at significant risk in future.
- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with habitable floor levels above the fluvial design flood event (1% AEP) taking into account climate change.
- If flood mitigation measures are implemented then they are tested to ensure that they will not displace water elsewhere (for example, if land is raised to permit development on one area, compensatory flood storage will be required in another).
- Safe access and egress can be demonstrated in the 1% AEP surface water, and fluvial events and 0.5% AEP tidal event, with an appropriate allowance for climate change, or an appropriate Flood Warning and Evacuation plan based on a policy of shelter-in-situ is agreed with the Local Councils’ Emergency Planner.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency’s Flood Map for Planning and high level 2D fluvial modelling undertaken as part of this SFRA.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency’s Flood Map for Planning mapping.
Climate change	High level 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model). Climate change allowances (for the 2080s) were modelled as part of Level 2 SFRA. This included Central (+11%), Higher central (+20%). For surface water a 1% AEP plus40% scenario has been considered.
Fluvial depth, velocity and hazard mapping	High level 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model) to provide fluvial depth, velocity and hazard mapping.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth and hazard mapping is taken Environment Agency’s Risk of Flooding from Surface Water mapping.



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN0274REVB
Address	The Street, Gillingham, South Norfolk, 40783 92035
Area	0.90ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment
The site is located in the River Waveney Catchment, between Ellingham Mill and Burgh St.Peter. The River Waveney flows from its source in the Regrave and Lopham Fen National Nature Reserve, through the towns of Harleston, Diss, Bungay and Beccles, and joins the River Yare before it reaches the sea at Great Yarmouth.

Existing drainage features
The site is located approximately 0.9km north-east of the River Waveney. The Environment Agency states that the reach section in which the site is located near is heavily modified, having undergone channel straightening and deepening over the years. Online imagery suggests there are a number of drainage ditches present on the site. Apart from those specified, there are no additional watercourses within the site boundary or near the site.

Fluvial

The proportion of site at risk (Environment Agency's Flood Map for Planning):
FZ3 – 60%
FZ2 – 64%
FZ1 – 36%

The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).

The proportion of site at risk (Gillingham Strategic Model – fluvial only):
1% AEP - 2%
0.1% AEP - 2%

Available data:
 High level 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model).
 The updated PPG defines the functional floodplain as land which would flood in the 3.3% AEP extent. As this was not available for the Gillingham Strategic model, Flood Zone 3a can be used as a conservative indication.

Flood characteristics:
 In all modelled fluvial scenarios, flood water flows along The Street adjacent to the south-western border of the site, crossing slightly into the site.
 In the 1% AEP event depths within the flow path along the boundary reach a maximum of 0.67m, with velocities of up to 3.0m/s and a maximum hazard classification of 'Danger for most'.
 In the 0.1% AEP event the maximum depths increase slightly to 0.70m, velocities remain up to 3.0m/s and the maximum hazard classification increases to 'Danger for all'. Whilst the site itself is not at significant risk, this flow path is likely to impact safe access/egress to the site.

Coastal and Tidal **Modelling:**

	<p>0.5% AEP – 0% 0.1% AEP – <1%</p> <p>Available data: High level 2D tidal modelling was undertaken in TUFLOW based on the application of water levels from Coastal Flood Boundary (CFB) Extreme Sea Levels dataset.</p> <p>Flood characteristics: The site is not shown to be at risk in the 0.5% AEP tidal event. In the 0.1% AEP tidal event, flood water just reaches the ditch at the southern corner of the site. maximum depths reach 0.14m, with velocities remaining below 0.1m/s and a maximum hazard classification of 'Very low hazard'. The majority of the site remains unaffected.</p>
Surface Water	<p>Proportion of site at risk (RoFSW): 3.3% AEP – 0% 1% AEP – 0% 0.1% AEP – <1%</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %)</i></p> <p>Description of surface water flow paths: The site is not affected by surface water flooding in the 3.3% or 1% AEP events. In the 0.1% AEP surface water event, a surface water flow path forms along the south-western boundary of the site adjacent to The Street and encroaches slightly on the southern corner of the site. Maximum depths within the flow path adjacent to the site are between 0.6m and 0.9m, with velocities of up to 1.0m/s. The maximum hazard classification is 'Danger for most'. Although the surface water risk to the site is minimal there are several significant surface water flow paths are present in the vicinity of the site- these are discussed further in the 'Access and Egress' section below.</p>
Reservoir	<p>The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.</p>
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding (AStWGF), provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The AStWGF map shows that most of the site has less than a 25% susceptibility to groundwater flood emergence. The southern corner of the site has between a 25% and 50% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater map emulates this, with the entire site shown to be at 'No risk'. This means that there is a negligible risk from groundwater flooding due to the nature of the local geological deposits.</p> <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	<p>The site is located in a postcode (NR34 0) with 15 recorded historic sewer flooding incidences between May 2013 and March 2024 according to information provided by Anglian Water.</p>
Flood history	<p>The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.</p>
Flood risk management infrastructure	
Defences	<p>This site is not protected by any formal flood defences.</p>
Residual risk	<p>There is no residual risk to the site from flood risk management structures.</p>
Emergency planning	
Flood warning	<p>The site is not located in an Environment Agency Flood Alert or Flood Warning Area.</p>
Access and egress	<p>The site is accessed via The Street which runs along the south-western border of the site. The Street can be accessed through Gillingham to the east or along Old Yarmouth Road and Geldeston Road from the west.</p>

	<p>Whilst The Street is not at significant risk from surface water where it runs adjacent to the site, there is surface water flood risk along The Street to the south of the site. Old Yarmouth Road and Geldeston Road are shown to be significantly impacted by a large surface water flow path in all modelled surface water events.</p> <p>In all modelled fluvial events, there is considerable flood risk across Geldeston Road and Yarmouth Road. There is also a flow path which forms along the site boundary adjacent to The Street. Therefore, access and egress to the site is likely to be impacted.</p> <p>Safe access and egress will need to be demonstrated in the 1% AEP plus climate change surface water event and fluvial events and the 0.5% AEP plus climate change tidal event. Ideally, the access route should be situated 300mm above the designed flood level and waterproofing techniques should be used where necessary. Raising of access routes must not impact on surface water flow routes.</p> <p>Consideration should be given to the siting of access points with respect to areas of flood risk. A Flood Warning and Evacuation plan should be in place for the site. Alternatively, risk could be managed by inclusion of a higher refuge and a flood response plan that meets the requirements of the Local Council and their Emergency Planner, considering the likely warning time and duration of flooding.</p>
--	---

Dry Islands	The site is not located on a dry island.
--------------------	--

Climate change	
-----------------------	--

Implications for the site	<ul style="list-style-type: none"> Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of surface water flooding. The central and higher climate change scenarios have been modelled as part of this assessment. Modelling suggests that the site will not be at significantly greater risk in the future, even during the 0.1% AEP event in the higher central scenario, although the flooding on The Street will increase in depth and velocity. In terms of tidal risk, the site is shown to be slightly sensitive to the impacts of climate change. The site is not impacted by tidal flooding in the 0.5% AEP present day event but in the 0.5% AEP 2122 higher central climate change event there is an area of tidal flood risk in the southern corner of the site. Depths on the site are predicted to reach a maximum of 0.7m. However, the rest of the site remains free from tidal risk. Climate change should also be considered for surface water events; at the site-specific stage, the 1% AEP +40% event is considered as part of surface water drainage strategies, or surface water modelling. The 1% AEP +40% event mapping suggests that the site is unlikely to be at increased risk of surface water flooding in future, although there remains a significant risk to the area around the site. Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
----------------------------------	--

Requirements for drainage control and impact mitigation	
--	--

Broad-scale assessment of possible SuDS	<p>Geology & Soils</p> <ul style="list-style-type: none"> Geology at the site consists of: <ul style="list-style-type: none"> Bedrock – Crag Group-Sand Superficial - Lowestoft Formation – Clay and Silt. Soils at the site consist of slightly acid loamy and clayey soils with impeded drainage. <p>SuDS</p> <ul style="list-style-type: none"> The site is not considered to be susceptible to groundwater flooding, due to the nature of the local geological conditions. This should be confirmed through additional site investigation work. Below ground development such as basements may still be susceptible to groundwater flooding. BGS data indicates that the underlying geology is chalk which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy. The entire site is located within a Groundwater Source Protection Zone 3. Infiltration techniques may not be suitable and should only be used following the granting of any
--	--

	<p>required environmental permits from the Environment Agency for Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints.</p> <ul style="list-style-type: none"> • The site is not located within a historic landfill site. • Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques. • The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 0.1% AEP event. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space. • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.
<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints. • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies. • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.
<p>NPPF and planning implications</p>	
<p>Exception Test requirements</p>	<p>The Local Authority will need to confirm that the Sequential Test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied.</p> <p>The NPPF classifies residential development as 'More Vulnerable'. As part of the site is in Flood Zone 3a, the Exception Test is required for the site.</p>
<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site is in Flood Zone 3a. • All sources of flooding, particularly the risk of fluvial and surface water, should be considered as part of a site-specific flood risk assessment. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich City Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority, Lead Local Flood Authority and the Environment Agency should be undertaken at an early stage. • The development should be designed to ensure that mitigation measures are in place to ensure the development does not flood, or that ground level space is used for less vulnerable parts of the development. <p>Guidance for site design and making development safe:</p>

- The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF's policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG).
- Safe access and egress will need to be demonstrated in the 1 % AEP plus climate change fluvial and rainfall events and the 0.5% AEP plus climate change tidal event, using the depth, velocity and hazard outputs. Ideally, the access route should be situated 300mm above the designed flood level and waterproofing techniques should be used where necessary. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk.
- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.
- Areas at risk from surface water flooding should ideally be integrated into green infrastructure, which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. Integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and to ensure that overland flows do not overwhelm future sustainable drainage features.
- The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA, IDB or Anglian Water).

Key messages

Development at the site is likely to be able to proceed if:

- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with habitable floor levels above the fluvial design flood event (1% AEP) taking into account climate change.
- If flood mitigation measures are implemented then they are tested to ensure that they will not displace water elsewhere (for example, if land is raised to permit development on one area, compensatory flood storage will be required in another).
- Safe access and egress can be demonstrated in the 1% AEP surface water and fluvial events and 0.5% AEP tidal event, with an appropriate allowance for climate change, or an appropriate Flood Warning and Evacuation plan based on a policy of shelter-in-situ is agreed with the Local Councils' Emergency Planner.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency's Flood Map for Planning and strategic 2D fluvial modelling undertaken as part of this SFRA.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	High level 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model). Climate change allowances (for the 2080s) were modelled as part of Level 2 SFRA. This included Central (+11%), Higher central (+20%). For surface water a 1%% AEP plus 40% scenario has been considered.
Fluvial depth, velocity and hazard mapping	Strategic 2D fluvial modelling of a key small watercourse identified running along the southern boundary of the proposed development site was undertaken in TUFLOW (Gillingham Strategic Model) to provide fluvial depth, velocity and hazard mapping.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity	The surface water depth and hazard mapping is taken Environment Agency's Risk of Flooding from Surface Water mapping.



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN2183REV
Address	Wymondham Road, Wreningham, Hethel, South Norfolk TM 15529, 98583
Area	1.2ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment	The site is located within the River Yare catchment, located within Wreningham, east of Wymondham. The eastern edge of the site is adjacent to an unnamed watercourse. This meets the confluence of an unnamed tributary of the River Tas 300m south of the site, which flows in an easterly direction. The northeast-southwest trending unnamed tributary meets the River Tas 4.5km southeast of the site.
--	---

Existing drainage features	Land at the site slopes down towards the east, as seen by local topography. This indicates drainage is in a west-east direction, towards the unnamed watercourse along the eastern site boundary.
-----------------------------------	---

Fluvial	<p>The proportion of site at risk: FZ3b – 0% FZ3a – 0% FZ2 – 0% FZ1 – 100%</p> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).</i></p> <p>Available data: The Environment Agency's (EA) Flood Maps for Planning have been used within this assessment.</p> <p>Flood characteristics: The site is not shown to be at risk of fluvial flooding which show the site is not located within Flood Zone 2 and 3, however the Environment Agency data does not cover watercourses with a catchment of less than 3km² and the site is very likely to be at risk of fluvial flooding from the unnamed watercourse on the eastern boundary. The Risk of Flooding from Surface Water (RoFfSW) gives an indication of the risk from smaller watercourses, and this is discussed below. It is recommended that detailed modelling is undertaken of the unnamed watercourse, including depth, velocity, and hazard outputs, to assess the risk to the site as part of a site-specific Flood Risk Assessment.</p>
----------------	---

Coastal and Tidal	The site is not at risk of tidal or coastal flooding.
--------------------------	---

Surface Water	<p>Proportion of site at risk (RoFfSW): 3.3% AEP – 45% Max depth- 0.3-0.6m Max velocity- 0.5-1.0m/s 1% AEP – 54% Max depth- 0.3-0.6m</p>
----------------------	--

	<p>Max velocity- 0.5-1.0m/s 0.1% AEP – 69% Max depth- 0.6-0.9m Max velocity- 1.0-2.0m/s</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %)</i></p> <p>Description of surface water flow paths: The site is shown to be at significant risk of surface water flooding in all modelled events. Flows are in a northwest-southeast direction across the north and east of the site, associated with the unnamed watercourse on the eastern boundary. Surface water flooding occurs in the 3.3%, 1% and 0.1% AEP events, extending 50, 55 and 67m in from the eastern edge of the site respectively. During the 0.1% AEP event, surface water flow paths cover approximately two thirds of the site. Surface water flooding is confined to the east of the site due to its shallower topography. During both the 3.3% and 1% AEP events, maximum flood depths are 0.3-0.6m and maximum velocities are 0.5-1.0m/s. This forms a maximum hazard of 'Danger for Most' in both events along the eastern edge of the site. During the 0.1% AEP event, surface water flood depths reach a maximum of 0.6-0.9m and maximum velocities are 1.0-2.0m/s. This correlates to a maximum hazard of 'Danger for Most' across the eastern half of the site. Due to significant surface water flood depths and velocities, it is advised that a detailed site-specific FRA is undertaken for this site in order to fully evaluate surface water risk.</p>
Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding dataset, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The AStGWF map shows that the entire site has a less than 25% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater map emulates this, with the entire site shown to be at 'No risk'. This means that there is a negligible risk from groundwater flooding due to the nature of the local geological deposits.</p> <p>This assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located in a postcode (NR16 1) with 30 recorded historic sewer flooding incidents, although only ten of these incidences have occurred since 2020.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	The site is not protected by any formal flood defences.
Residual risk	The unnamed watercourse running along the eastern edge of the site is culverted under Ashwellthorpe Road 100m east of the site. This poses a residual risk to the site since if this culvert were to become blocked, water could back up and encroach onto the site. This would particularly impact the east of the site due to its proximity to the unnamed watercourse and shallow topography. The watercourse is also culverted under the same road 460m south of the site, which could also be of residual risk to the site in the event of a blockage
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Warning Area.
Access and egress	A heavy metal field gate leading from Wymondham Road provides direct access to the north of the site. The unnamed road leading from Ashwellthorpe Road next to 'Wreningham Stables Dressage' could provide access by emergency vehicles to the south of the site. Due to the extensive surface water flows across the north and east of the site, access from the gate at Wymondham Road is likely to be significantly impacted during the 3.3%, 1% and 0.1% AEP events. The access point has a hazard of 'danger for most' during the 0.1%

	<p>AEP event. Any access via Ashwellthorpe road is also likely to be significantly impacted during all events, with depths of 0.3-0.6m present in the 0.1% AEP surface water event. Access may still be possible during the 3.3% and 1% AEP events where depths and velocities are lower. Developers will need to demonstrate safe access and egress during the 0.1% AEP event and raising of access routes must not impeded surface water flows. Since safe access and egress to the site is likely to be impeded in all surface water flood events, a Flood Warning and Evacuation Plan should be prepared for the site, including considering a policy of shelter in situ, which may or may not be appropriate depending on the extent and durations of flooding indicated by detailed modelling.</p>
<p>Dry Islands</p>	<p>The site is not located on a dry island.</p>
<p>Climate change</p>	
<p>Implications for the site</p>	<ul style="list-style-type: none"> • Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding. • The 1% AEP surface water event with a 40% allowance for climate change was available for use in this assessment to assess the potential implications of climate change on surface water flood risk at the site. • There is a considerable increase in the extent of flooding on site between the 1% and 1% AEP plus 40% climate change event with the flow path extending approximately 10m further west into the site, suggesting that the site is sensitive to effects of climate change. This would require a detailed Flood Risk Assessment (FRA) to assess the site layout and design. • The site is likely to be at risk from the unnamed watercourse on the eastern boundary and detailed modelling, applying the latest climate change allowances, should be undertaken as part of a site-specific FRA. • Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA. • A site-specific FRA, with the most up-to-date climate change allowances, should be undertaken to investigate the implications of climate change on the site.
<p>Requirements for drainage control and impact mitigation</p>	
<p>Broad-scale assessment of possible SuDS</p>	<p>Geology & Soils</p> <ul style="list-style-type: none"> • Geology at the site consists of: <ul style="list-style-type: none"> ○ Bedrock- Lewes Nodular Chalk Formation, Seaford Chalk Formation, Newhaven Chalk Formation, Culver, Chalk Formation and Portsmouth Chalk Formation. ○ Superficial- Lowestoft Formation- Diamicton. • Soils at the site consist of: <ul style="list-style-type: none"> ○ Slightly acid loamy and clayey soils with impeded drainage. <p>SuDS</p> <ul style="list-style-type: none"> • The site is considered to have very low susceptibility to groundwater flooding, this should be confirmed through additional site investigation work. Below ground development such as basements may still be susceptible to groundwater flooding. • BGS data indicates that the underlying geology is chalk which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy. • The site is not located within a Groundwater Source Protection Zone and there are no restrictions over the use of infiltration techniques with regard to groundwater quality. • The site is not located within a historic landfill site. • Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques. • The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 3.3%, 1% and 0.1% AEP event. Existing

	<p>flow paths should be retained and integrated with blue-green infrastructure and public open space.</p> <ul style="list-style-type: none"> • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.
<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints. • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies. • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.
<p>NPPF and planning implications</p>	
<p>Exception Test requirements</p>	<p>The Local Authority will need to confirm that the sequential test has been carried out in line with national guidelines. The Sequential Test will need to be passed before the Exception Test is applied.</p> <p>The entire sites is located outside of the fluvial flood zones, however, as the site is at significant risk of surface water flooding from the watercourse on the eastern boundary the Exception Test should be applied at this site.</p> <p>The Exception Test is needed if:</p> <ul style="list-style-type: none"> • 'More vulnerable' development in Flood Zone 3a • 'Essential infrastructure' in Flood Zone 3a or 3b • 'Highly vulnerable' development in Flood Zone 2 • Any development where a higher risk of surface water has been identified (surface water Zone B) and the site does not clearly show that development can be achieved away from the flood risk. •
<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • A site-specific Flood Risk Assessment is required at this site as the development is greater than one hectare and at significant risk of surface water flooding. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance; the Joint Core Strategy as part of the Greater Norwich Development Partnership for Broadland, Norwich and South Norwich; and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • The unnamed watercourse on the eastern boundary should be modelled as part of the site-specific FRA, including depth, velocity, and hazard outputs. Modelling should include the latest climate allowances. • Consultation with the Local Authority and the Lead Local Flood Authority should be undertaken at an early stage. <p>Guidance for site design and making development safe:</p>

- The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF's policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG).
- The development should be designed using a sequential approach. Development should be steered away from areas of flood risk along the north and east of the site, preserving these spaces as green infrastructure. This is likely to significantly limit the area available for development.
- Safe access and egress will need to be demonstrated in the 0.1% AEP event plus climate change fluvial and rainfall events, using the depth, velocity and hazard outputs. Ideally, the access route should be situated 300mm above the designed flood level and waterproofing techniques should be used where necessary. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk. Due to the significant surface water flood risk posed to the site, a Flood Warning and Evacuation Plan must be prepared, including an assessment of the suitability of a shelter in situ policy using model outputs.
- Flood resilience and resistance measures should be implemented wherever possible during the construction phase, e.g. raising of floor levels and use of boundary walls.
- The risk from surface water flow routes should be quantified as part of a site specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.
- On site attenuation schemes would need to be tested to ensure flows are not exacerbated downstream within the catchment.
- Surface water should be discharged at the pre-development (greenfield) runoff rate which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. An integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and to ensure that overland flows do not overwhelm future sustainable drainage features.
- Developers should refer to Norfolk County Council's 'Norfolk County Council Lead Local Flood Authority Statutory Consultee for Planning Guidance Document' and the Level 1 SFRA for information on SuDS for guidance on the information required by the LLFA from applicants to enable it to provide responses to planning applications.

Key messages

The site is at considerable risk from fluvial/surface water flooding associated with the unnamed watercourse on the eastern boundary of the site, which is likely to severely limit the area available for development. Development is likely to be able to proceed if:

- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with development to be steered away from the north and east of the site.
- Where development is proposed within areas of risk, habitable floor levels should be above the fluvial design flood event (1% AEP) taking into account climate change. This level should be in line with the latest guidance. Ground floor dwelling should be avoided where possible and waterproofing techniques should be used where necessary.
- A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA or Anglian Water).
- Space for surface water to be stored on the site is provided and rainwater harvesting should be considered.
- A site-specific Flood Risk Assessment demonstrates that the site is not at an increased risk of flooding in the future as a result of climate change, and that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties.

- If flood mitigation measures are implemented, they should be tested to ensure water is not displaced elsewhere.
- Safe access and egress is likely to be impacted during the 3.3%, 1% and 0.1% AEP events. Therefore, a Flood Warning and Evacuation Plan should be prepared for this site for both present day and considering climate change allowances. Consideration should be given to the siting of safe access and egress routes, and these must not impede surface water flows risk.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	In the absence of detailed modelling, the Environment Agency's Flood Map for Planning Flood Zone 2 has been used as an indication of flood extent during a 1% + climate change. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	No fluvial modelling is available for the unnamed watercourse on the eastern boundary of the site. The Environment Agency's Risk of Flooding from Surface Water map has been used to give an indication of the likely flood extents from this watercourse.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, hazard and velocity mapping are taken from the Environment Agency's Risk of Flooding from Surface Water mapping



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN2118
Address	Sneath Road, Sneath Common, TM 15544 89271
Area	0.54ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment	The site is located within the River Tas catchment. The River Tas flows north from its source, near Carleton Fen, and through Long Stratton before joining the River Yare at Trowse. The River Yare then continues eastwards until it reaches the North Sea at Great Yarmouth.
--	--

Existing drainage features	The site is located approximately 2.4km south of the River Tas, an ordinary watercourse. The Environment Agency states that this 16.7km river is not heavily modified. Online imagery suggests there are also a number of drainage ditches in the area. Local topography shows the site at a higher relief compared to land located further north, this indicates that drainage from the site would be in a northerly direction.
-----------------------------------	--

Fluvial	<p>The proportion of site at risk: FZ3b – 0% FZ3a – 0% FZ2 – 0% FZ1 – 100%</p> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).</i></p> <p>Available data: The Environment Agency's (EA) Flood Maps for Planning have been used within this assessment.</p> <p>Flood characteristics: The site is not currently at risk of flooding from fluvial sources. The Environment Agency's Flood Mapping for Rivers and Sea does not show the site to be within flood zone 2 or 3 and there are no other watercourses in the vicinity of the site which are likely to pose a risk to the site.</p>
----------------	--

Coastal and Tidal	The site is not at risk of tidal or coastal flooding.
--------------------------	---

Surface Water	<p>Proportion of site at risk (RoFfSW): 3.3% AEP – 0% 1% AEP – 0% 0.1% AEP – 42% Max depth - 0.30m Max velocity - 1.0m/s</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %).</i></p>
----------------------	---

	<p>Description of surface water flow paths:</p> <p>During the 3.3% AEP event, there is no surface water flooding predicted within the proposed site. There is a small ponding of surface water at the junction between Sneath and Plantation Road, but the depth of this flooding is modelled to be at maximum 0.15m. Maximum velocities are shown to be 1m/s. Safe access and egress to the site will therefore not be affected.</p> <p>During the 1% AEP event, there is no surface water flooding predicted within the proposed site. The ponding shown in the 3.3% event extends further down Plantation Road and back into Sneath Road, however, this flooding depth will only be 0.30m at maximum. Therefore, emergency vehicles will still be able to access the site via these roads. Maximum velocities are shown to be 1m/s.</p> <p>In event of a 0.1% AEP flood, there is significant surface water pooling predicted within the site. There is also a surface water flow path along the northern boundary of the site, which extends down Plantation Road, along the site's western boundary. Local LiDAR data indicates that this flow path flows northwards. The pooling within the site has a maximum flood depth of 0.30m and a maximum velocity of 1m/s. The same maximum depths are present for the surface water flow path, however the maximum velocity is 2m/s.</p> <p>Flooding in all scenarios is classified as 'Very Low Hazard'.</p>
Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding dataset, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The entire site has a <25% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater map emulates this, with the entire site shown to be at 'No risk'. This means that there is a negligible risk from groundwater flooding due to the nature of the local geological deposits.</p> <p>This assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located within a postcode (NR15 2) shown to have 84 recorded instances of sewer flooding between May 2013 and March 2024 according to information provided by Anglian Water.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	The site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Warning Area
Access and egress	<p>The site is currently accessible from Sneath and Plantation Road. The site is likely to remain accessible in all modelled flood scenarios as flood depths are shown to be 0.30m at maximum, with a maximum hazard of 'Very Low'. Therefore, emergency vehicles will be able to have safe access and egress to the site.</p> <p>The depths, velocities, hazards, durations and speeds of onset of surface water along access/egress routes should be investigated further in a site-specific assessment, to confirm whether access for emergency vehicles could still be obtained.</p> <p>As surface water events are typically flashy and short-lived, it is likely that access to the site will only be affected for a short period of time.</p>
Dry Islands	The site is not located on a dry island.
Climate change	

Implications for the site

- The 1% AEP surface water event with a 40% allowance for climate change was available for use within this assessment.
- There is a considerable increase in the extent of flooding on the site between the 1% and 1% AEP plus 40% climate change surface water event, with a new area of ponding developing in the centre of the site. This indicates the site is very sensitive to the effects of climate change. This would require a detailed Flood Risk Assessment to assess the site layout and design. In addition to the SuDS features designed to accommodate runoff from new development infrastructure the proposals should also address the potential loss of natural storage of rainfall and runoff provided by the land in its natural condition.
- Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific Flood Risk Assessment.
- The nearest watercourse to the site is approximately 300m to the north. As the site is significantly elevated above the site, it is very unlikely that the site will be at increased risk of fluvial flooding in future.

Requirements for drainage control and impact mitigation

Broad-scale assessment of possible SuDS

Geology & Soils

- Geology at the site consists of:
 - Bedrock- Lewes Nodular Chalk Formation, Seaford Chalk Formation, Newhaven Chalk Formation, Culver Chalk Formation and Portsdown Chalk Formation (undifferentiated) –Chalk.
 - Superficial- Lowestoft Formation- Diamicton.
- Soils at the site consist of:
 - Loamy and clayey soils- moderate fertility, impeded drainage

SuDS

- The site is considered to have very low susceptibility to groundwater flooding, this should be confirmed through additional site investigation work. Below ground development such as basements may still be susceptible to groundwater flooding.
- BGS data indicates that the underlying geology is chalk which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy.
- The site is not located within a historic landfill site.
- Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques.
- The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 0.1% AEP events. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space.
- If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.

Opportunities for wider sustainability benefits and integrated flood risk management

- Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints.
- Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development.
- Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies.

	<ul style="list-style-type: none"> • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.
--	---

NPPF and planning implications

Exception Test requirements	<p>The Local Authority will need to confirm that the sequential test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied. The NPPF classifies residential development as 'More Vulnerable'.</p> <p>As the site is in Flood Zone 1 but affected by surface water flood risk the Exception Test is required.</p>
------------------------------------	--

Requirements and guidance for site-specific Flood Risk Assessment	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • Although the site is not located in a Flood Zone, a large proportion of the site is subject to surface water flooding in event of a 0.1% AEP. Therefore, it is recommended that a precautionary approach is taken, and a site-specific flood risk assessment undertaken, including an assessment of future surface water flood risk accounting for climate change. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich City Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority, Lead Local Flood Authority and the Environment Agency should be undertaken at an early stage. <p>Guidance for site design and making development safe:</p> <ul style="list-style-type: none"> • The development should be designed using a sequential approach. • Safe access and egress will need to be demonstrated in the 1% AEP plus climate change rainfall event, using the depth, velocity and hazard outputs. Raising of access routes must not impact on surface water flow routes. Consideration should be given to the siting of access points with respect to areas of surface water flood risk. • The risk from surface water flow routes should be quantified as part of a site-specific Flood Risk Assessment, including a drainage strategy, to ensure that runoff from the development is not increased by placing development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond the current greenfield rates. • It is recommended that finished floor levels are raised above ground level, in line with current EA guidance, to prevent surface water flooding within the site. Raising Finished Floor Levels may remove the need for resilience measures. • On site attenuation schemes would need to be tested to ensure flows are not exacerbated downstream within the catchment. • New or re-development should adopt exemplar source control SuDS techniques to reduce the risk of frequent low impact flooding due to post-development runoff. Assessment for runoff should include allowance for climate change effects. • Surface water runoff should be fully attenuated to the greenfield rate to ensure that there is no increase in surface water flood risk elsewhere. • Developers should refer to Norfolk County Council's 'Norfolk County Council Lead Local Flood Authority Statutory Consultee for Planning Guidance Document' and the Level 1 SFRA for information on SuDS for guidance on the information required by the LLFA from applicants to enable it to provide responses to planning applications.
--	---

Key messages

The development is likely to be able to proceed if:

- A site-specific Flood Risk Assessment demonstrates that the site is not at an increased risk of flooding in the future as a result of climate change, and that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties.
- Finished floor levels are raised in line with current EA guidance, to prevent surface water flooding on site.
- The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate.
- A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.
- Safe access and egress can be demonstrated in the 1% AEP plus climate change surface water event.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	In the absence of detailed modelling, the Environment Agency's Flood Map for Planning Flood Zone 2 has been used as an indication of flood extent during a 1% + climate change scenario. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	This site is not shown to be at significant risk of flooding from fluvial sources.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, hazard and velocity mapping are taken from the Environment Agency's Risk of Flooding from Surface Water mapping



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN1015REV
Address	The Street, Hempnall, South Norfolk TM 23903, 94666
Area	1.2ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment
The site is located within the Yare catchment and is located 10km south of the River Yare. The Hempnall Beck runs east-west 45m south of the site before meeting its confluence with the River Tas 4.5km northwest of the site. An unnamed tributary of the Hempnall Beck is located 250m southwest of the site. The Hempnall Beck has not been designated artificial or heavily modified.

Existing drainage features
The north of the site is of higher relief than the south of the site, meaning the site slopes downwards towards the south. The south-bearing sloped surface of the site indicates drainage is towards the east-west trending Hempnall Beck just south of the site.

Fluvial
The proportion of site at risk:
FZ3b – 0%
FZ3a – 0%
FZ2 – 0%
FZ1 – 100%
The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).

Available data:
The Environment Agency’s (EA) Flood Maps for Planning have been used within this assessment.

Flood characteristics:
The site is not currently at risk of fluvial flooding. The EA’s Flood Maps for Planning show the site is not located within Flood Zone 2 and 3. The land 70m south of the site, along the Hempnall Beck, falls within both Flood Zone 2 and 3. This is currently unlikely to affect the site but should be considered when considering the implications of climate change on the site.

Coastal and Tidal
The site is not at risk of tidal or coastal flooding.

Surface Water
Proportion of site at risk (RoFFSW):
3.3% AEP – 0%
1% AEP – 1%
Max depth - 0.15 - 0.30m
Max velocity - 0.00 – 0.25m/s
0.1% AEP – 22%
Max depth – 0.30 – 0.60m
Max velocity - 0.50 – 1.00m/s

	<p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %).</i></p> <p>Description of surface water flow paths:</p> <p>The site is not predicted to be at risk of surface water flooding during the 3.3% AEP event. A surface water pond is predicted to occur during the 1% AEP event 10m from the southern site boundary. This isolated pond is 17m in diameter. The surface water extent is much wider during the 0.1% AEP event. A much larger pond, of diameter 90m, occurs near the southern site boundary adjacent to The Street. A surface water flow path cuts across the northwest site boundary, entering 18m in from the northwest corner.</p> <p>During the 1% AEP event, the predicted maximum flood water depth of the pond towards the south of the site is 0.15-0.3m and maximum velocities are 0.00-0.25m/s. This forms a maximum hazard of 'Very low hazard' in this area. Maximum flood depths during the 0.1% AEP event are 0.3-0.6m at the pond near the southern site boundary. Maximum velocities are 0.5-1.0m/s at the northwest corner of the site. The resulting hazard is 'Danger for most' at the pond towards the south of the site.</p>
Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding (AStWGF), provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The AStGWF map shows that around three quarters of the site, the western, northern and southern areas, has between a 25 and 50% susceptibility to groundwater flood emergence. Furthermore, the very eastern corner of the site has a less than 25% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater map indicates predicted groundwater levels are between 0.5 and 5m below the ground surface for the entire site. This means that there is a risk of flooding to subsurface assets, but surface manifestation of groundwater is unlikely.</p> <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located in a postcode (NR15 2) with 84 recorded historic sewer flooding incidents, although only 24 of these incidences have occurred since 2020.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	The site is protected from flooding by high ground on either side of the Hempnall Beck south of the site. The upstream reach of the Hempnall Beck is not protected by any formal flood defences.
Residual risk	There is a residual risk to the south of the site if floodwater overtops the high ground adjacent to the Hempnall Beck. In such an event, the southern half of the site is likely to become inundated with floodwater due to the low-lying topography.
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Warning Area.
Access and egress	<p>An unnamed road-access path, leading from The Street, provides direct access from the south of the site to the western edge and centre. The east of the site can also be accessed from grounds of the Hempnall Primary School.</p> <p>The site remains accessible by emergency vehicles along the road-access path leading through the site during the 1% AEP event. Access via the school grounds is still possible during this event. However, safe access and egress is impeded during the 0.1% AEP event in which the region to the south of the site has a maximum hazard of 'danger for most'. The large surface water pond at the south of the site crosses over the road access path and partially blocks access via the school grounds. Access may still be possible by emergency vehicle via the school grounds, but this should be further investigated at site-specific FRA stage.</p>

Dry Islands	The site is not located on a dry island.
Climate change	
Implications for the site	<ul style="list-style-type: none"> Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding. The 1% AEP event with a 40% allowance for climate change was made available for this assessment. There is a significant increase in the extent of the surface water ponding in the southern end of the site between the 1% and 1% AEP plus 40% climate change event, suggesting the site is very sensitive to increased runoff as a result of climate change. This would require a detailed Flood Risk Assessment (FRA) to assess the site layout and design. In addition to the SuDs features designed to accommodate runoff from new development infrastructure the proposals should also address the potential loss of natural storage of rainfall and runoff provided by the land in its natural condition. Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA. A site-specific FRA, with the most up-to-date climate change allowances, should be undertaken to investigate the implications of climate change on the site.
Requirements for drainage control and impact mitigation	
Broad-scale assessment of possible SuDS	<p>Geology & Soils</p> <ul style="list-style-type: none"> Geology at the site consists of: <ul style="list-style-type: none"> Bedrock- Norwich Crag Formation. Superficial- Leet Hill Sand and Gravel Member- Sand and Gravel. Soils at the site consist of: <ul style="list-style-type: none"> Slightly acid loamy and clayey soils with impeded drainage <p>SuDS</p> <ul style="list-style-type: none"> The site is considered to have a low susceptibility to groundwater. Detention and attenuation features should be designed to prevent groundwater ingress from impacting hydraulic capacity and structural integrity. Groundwater monitoring is recommended to determine the seasonal variability of groundwater levels, as this may affect the design of the surface water drainage system. Below ground development such as basements may not be appropriate at this site. BGS data indicates that the underlying geology is a combination of sands and mud which is likely to be with highly variable permeability. This should be confirmed through infiltration testing. Off-site discharge in accordance with the SuDS hierarchy may be required to discharge surface water runoff from the site. The site is not located within a historic landfill site. The entire site is located within a Groundwater Source Protection Zone 3. Infiltration techniques may not be suitable and should only be used following the granting of any required environmental permits from the Environment Agency for Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints. Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques. The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 1% and 0.1% AEP events. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space.

	<ul style="list-style-type: none"> • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.
<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints. • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies. • Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site. • The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows
<p>NPPF and planning implications</p>	
<p>Exception Test requirements</p>	<p>The Local Authority will need to confirm that the sequential test has been carried out in line with national guidelines. The Sequential Test will need to be passed before the Exception Test is applied.</p> <p>The entire site lies outside of Flood Zone 2 and 3, but as it is predicted to be affected by surface water, the Exception Test applies.</p>
<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • Whilst the site lies entirely outside of Flood Zones 2 and 3, it is recommended that a site-specific Flood Risk Assessment is undertaken to provide evidence that the proposals satisfy the Exception Test due to surface water ponding within the site. • The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance; the Joint Core Strategy as part of the Greater Norwich Development Partnership for Broadland, Norwich and South Norwich; and the Norfolk County Council Lead Local Flood Authority’s Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority and the Lead Local Flood Authority should be undertaken at an early stage. <p>Guidance for site design and making development safe:</p> <ul style="list-style-type: none"> • The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF’s policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG). • Development should be steered away from the south of the site where surface water ponding occurs. Ideally, this area will be preserved as green infrastructure. • Safe access and egress will need to be demonstrated in the 1% AEP event plus climate change fluvial and rainfall events, using the depth, velocity and hazard outputs. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should particularly be given to the siting of access points with respect to areas of surface water flood risk.

- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.
- Surface water should be discharged at the pre-development (greenfield) runoff rate which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. An integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and to ensure that overland flows do not overwhelm future sustainable drainage features.
- Developers should refer to Norfolk County Council's 'Norfolk County Council Lead Local Flood Authority Statutory Consultee for Planning Guidance Document' and the Level 1 SFRA for information on SuDS for guidance on the information required by the LLFA from applicants to enable it to provide responses to planning applications.

Key messages

The development is likely to be able to proceed if:

- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with development to be steered away from low-lying region at the south of the site, if possible.
- Space for surface water to be stored on the site is provided and rainwater harvesting should be considered.
- A site-specific Flood Risk Assessment demonstrates that the site is not at an increased risk of flooding in the future, and that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties. Consideration to the implications of climate change should be given in this assessment.
- A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA or Anglian Water).
- Safe access and egress cannot currently be demonstrated during the 0.1% AEP event due to surface water ponding along the road access path. A Flood Warning and Evacuation Plan should therefore be prepared for this site for both present day and considering climate change allowances. Consideration should be given to the siting of safe access and egress routes, and these must not impede surface water flows risk.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	In the absence of detailed modelling, the Environment Agency's Flood Map for Planning Flood Zone 2 has been used as an indication of flood extent during a 1% + climate change scenario. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	This site is not shown to be at significant risk of flooding from fluvial sources.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, hazard and velocity mapping are taken from the Environment Agency's Risk of Flooding from Surface Water mapping



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN0488REV
Address	School Lane, Little Melton, Norwich, Norfolk TG 16786, 07356
Area	1.3ha
Current land use	Greenfield
Proposed land use	Residential

Location of the site within the catchment	The site lies within the River Yare catchment towards the north of the South Norfolk District. The west-east trending River Yare is located 880m north of the site and follows the district boundary 1km east of the site. An unnamed watercourse 1km south of the site flows east to meet the River Yare 1.9km southeast of the site.
--	--

Existing drainage features	Local topography shows the northern boundary of the site is at higher relief than the southern edge of the site. High relief 200m west of the site indicates drainage from the site would be in an easterly direction towards the River Yare.
-----------------------------------	---

Fluvial	<p>The proportion of site at risk: FZ3b – 0% FZ3a – 0% FZ2 – 0% FZ1 – 100%</p> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).</i></p> <p>Available data: The Environment Agency’s (EA) Flood Maps for Planning have been used within this assessment.</p> <p>Flood characteristics: The site is not currently at risk of fluvial flooding. The EA’s Flood Maps for Planning show the site is not located within Flood Zone 2 and 3.</p>
----------------	---

Coastal and Tidal	The site is not at risk of tidal or coastal flooding.
--------------------------	--

Surface Water	<p>Proportion of site at risk (RoFfSW): 3.3% AEP – 3% Max depth- 0.3-0.6m Max velocity- 0.0-0.25m/s 1% AEP – 13% Max depth- 0.9-1.2m Max velocity- 0.5-1.0m/s 0.1% AEP – 24% Max depth- >1.2m Max velocity- 1.0-2.0m/s</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %).</i></p>
----------------------	--

	<p>Description of surface water flow paths:</p> <p>The site is predicted to be at risk of surface water flooding during the 3.3%, 1% and 0.1% AEP events. Flooding is confined to the southern site boundary, with flow paths running adjacent to School Lane along the region of low topography. Surface water flood extents reach 16m, 30m and 38m in from the south of the site during the 3.3%, 1% and 0.1% AEP events respectively. Flow paths start to pond slightly in the southeast corner of the site. The rest of the site is free from surface water flooding due to higher relief.</p> <p>During the 3.3% AEP event, predicted maximum flood depths are 0.3-0.6m and maximum velocities are 0.0-0.25m/s along School Lane. This corresponds to a hazard of 'danger for some' in the southeast corner of the site. During the 1% AEP event, flood depths reach a maximum of 0.9-1.2m and velocities 0.5-1.0m/s. This forms a maximum hazard of 'danger for most' in the southeast of the site. Maximum flood depths are >1.2m and maximum velocities 1.0-2.0m/s, resulting in a maximum hazard of 'danger for most' across the southeast corner of the site.</p>
Reservoir	The Environment Agency online maps show the site is not shown to be at risk of reservoir flooding during the 'Dry Day' or 'Wet Day' scenarios.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding dataset, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The AStGWF map shows that the entire site has a less than 25% susceptibility to groundwater flood emergence.</p> <p>The JBA Groundwater map indicates predicted groundwater levels are between 0.5m and 5m below the ground surface for the north, east, and west of the site. In these areas there is a risk of flooding to subsurface assets but surface manifestation of groundwater is unlikely. The southwest of the site is classified as 'No risk'. This area is deemed as having a negligible risk from groundwater flooding due to the nature of the local geological deposits.</p> <p>The 0.1% AEP surface water flood extents highlight the potential for groundwater emerging in the southwest of the site to flow overland in an easterly direction along the southern boundary of the site, with potential to impact access to and egress from the site.</p> <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located in a postcode (NR9 3) with 83 recorded historic sewer flooding incidents between May 2013 and March 2024 according to information from Anglian Water, although only 23 of these incidences has occurred since 2020.
Flood history	The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.
Flood risk management infrastructure	
Defences	The site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Warning Area.
Access and egress	<p>The southwest corner of the site is accessible via a road-access path directly into the site. The site is fully accessible during fluvial flood events by vehicles and on foot. This access point however is not fully accessible during the 3.3%, 1% and 0.1% AEP events due to a surface water flow path along School Lane. During the 3.3% AEP event maximum flood depths are 0.15-0.3m which correlates to a maximum hazard of 'caution' at the southwest of the site. This means the road-access path to the southwest of the site may still be accessible by larger emergency vehicles. This access point remains inaccessible to large emergency vehicles in the 1% and 0.1% AEP event.</p> <p>Since safe access and egress to the site may not be safely possible in all flood events, a Flood Warning and Evacuation Plan should be prepared for the site, with a policy of shelter in situ.</p>
Dry Islands	The site is not located on a dry island.

Climate change

Implications for the site

- Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding.
- The 1% AEP plus 40% climate change extent was available for use in this assessment and provides an indication of the implications of climate change on surface water flood risk.
- There is an increase in the extent of flooding in the southeast corner of the site between the 1% and 1% AEP plus 40% surface water climate change events, with the area of risk extending up to 10m further into the site, indicating the site is sensitive to increasing runoff as a result of climate change. This would require a detailed Flood Risk Assessment (FRA) to assess the site layout and design. In addition to the SuDs features designed to accommodate runoff from new development infrastructure, the proposals should also address the potential loss of natural storage of rainfall and runoff provided by the land in its natural condition.
- Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
- A site-specific FRA, with the most up-to-date climate change allowances, should be undertaken to investigate the implications of climate change on the site.

Requirements for drainage control and impact mitigation

Broad-scale assessment of possible SuDS

Geology & Soils

- Geology at the site consists of:
 - Bedrock- Chalk Formation, Newhaven Chalk Formation, Seaford Formation, Culver Chalk, Formation and Portsdown Chalk Formation.
 - Superficial- Happisburgh Glacigenic Formation and Lowestoft Formation- Sand and Gravel; and Lowestoft Formation- Diamicton.
- Soils at the site consist of:
 - Slightly acid loamy and clayey soils with impeded drainage

SuDS

- The site is considered to have very low susceptibility to groundwater flooding, this should be confirmed through additional site investigation work. Below ground development such as basements may still be susceptible to groundwater flooding.
- BGS data indicates that the underlying geology is chalk which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy.
- The entire site is located within a Groundwater Source Protection Zone 3. Infiltration techniques may not be suitable and should only be used following the granting of any required environmental permits from the Environment Agency for Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints.
- The site is not located within a historic landfill site.
- Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques.
- The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 3.3%, 1% and 0.1% AEP events. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space.
- If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.

Opportunities for wider sustainability benefits and integrated flood risk management

- Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints.
- Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development.
- Opportunities to incorporate filtration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies.
- Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site.
- The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.

NPPF and planning implications

Exception Test requirements

The Local Authority will need to confirm that the sequential test has been carried out in line with national guidelines. The Sequential Test will need to be passed before the Exception Test is applied.

The entire site lies outside of Flood Zone 2 and 3 but as it is predicted to be affected by surface water risk the Exception Test is required.

Requirements and guidance for site-specific Flood Risk Assessment

Flood Risk Assessment:

- A site-specific flood risk assessment is required as the site is greater than one hectare and at risk of surface water flooding.
- The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance; the Joint Core Strategy as part of the Greater Norwich Development Partnership for Broadland, Norwich and South Norwich; and the Norfolk County Council Lead Local Flood Authority’s Statutory Consultee for Planning Guidance Document.
- Consultation with the Local Authority and the Lead Local Flood Authority should be undertaken at an early stage.

Guidance for site design and making development safe:

- The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF’s policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG).
- The development should be designed using a sequential approach. Development should be steered away from areas of surface water flood risk along the southern site boundary, preserving these spaces as green infrastructure.
- Safe access and egress will need to be demonstrated in the 1% AEP event plus climate change fluvial and rainfall events, using the depth, velocity and hazard outputs. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk.
- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.

- On site attenuation schemes would need to be tested to ensure flows are not exacerbated downstream within the catchment.
- Surface water should be discharged at the pre-development (greenfield) runoff rate which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. An integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and to ensure that overland flows do not overwhelm future sustainable drainage features.
- Developers should refer to Norfolk County Council's 'Norfolk County Council Lead Local Flood Authority Statutory Consultee for Planning Guidance Document' and the Level 1 SFRA for information on SuDS for guidance on the information required by the LLFA from applicants to enable it to provide responses to planning applications.

Key messages

The development is likely to be able to proceed if:

- A carefully considered and integrated flood resilient and sustainable drainage design is put forward, with development to be steered away from the southern site boundary.
- Space for surface water to be stored on the site is provided and rainwater harvesting should be considered.
- A site-specific Flood Risk Assessment demonstrates that the site is not at an increased risk of flooding in the future, and that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties.
- A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA or Anglian Water).
- If flood mitigation measures are implemented, they should be tested to ensure water is not displaced elsewhere.
- Since surface water flow paths occur along School Lane at the southern site boundary, access and egress is not possible during the 1% and 0.1% AEP events. A Flood Warning and Evacuation Plan should therefore be prepared for this site for both present day and considering climate change allowances. Consideration should be given to the siting of safe access and egress routes, and these must not impede surface water flows risk.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the broadscale 2D modelling outputs from the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	In the absence of detailed modelling, the Environment Agency's Flood Map for Planning Flood Zone 2 has been used as an indication of flood extent during a 1% + climate change scenario. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	This site is not shown to be at significant risk of flooding from fluvial sources.
Surface Water	The Risk of Flooding from Surface Water map has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, hazard and velocity mapping are taken from the Environment Agency's Risk of Flooding from Surface Water mapping



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	SN0262
Address	Land North of Church Road, Woodton, South Norfolk, 629339, 294692
Area	1.045ha
Current land use	Greenfield
Proposed land use	Residential

Sources of flood risk

Location of the site within the catchment	The site is located in the Broome Beck Catchment, North of Woodton. The Broome Beck flows from its source in Bedingham, east, past Woodton, and joins the River Waveney at Broome.
Existing drainage features	The site is located approximately 0.2km north-west of Woodton Stream, a tributary of the Broom Beck. Apart from those specified, there are no additional watercourses within the site boundary or near the site.
Fluvial	<p>The proportion of site at risk (Environment Agency's Flood Map for Planning Flood Zones): FZ3b – 0% FZ3a – 0% FZ2 – 0% FZ1 – 100%</p> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).</i></p> <p>Available data: The Environment Agency's (EA) Flood Map for Planning has been used within this assessment.</p> <p>Flood characteristics: The EA's Flood Map for Planning shows the site is not located in Flood Zones 2 and 3.</p>
Surface Water	<p>Proportion of site at risk (Environment Agency's RoFSW dataset): 3.3% AEP – 8.20% Max depth – 0.30 – 0.60m Max velocity – 0.25 – 0.50m/s 1% AEP – 8.90% Max depth – 0.30 – 0.60m Max velocity – 0.25 – 0.50m/s 0.1% AEP – 15.4% Max depth – 0.30 – 0.60m Max velocity – 0.50 – 1.00m/s</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a greater Annual Exceedance Probability (e.g. 1% AEP %includes the 3.3% AEP %)</i></p>

	<p>Description of surface water flow paths:</p> <p>The site is affected by surface water flooding in the 3.3%, 1% and 0.1% AEP event. In the 3.3% AEP and 1% AEP surface water events, water ponds in the lower lying south-east corner of the site. In the 0.1% AEP event, a small surface water flow forms between Woodton Stream and the south-east corner of the site. Depths are largely between 0.01-0.15m along the flow path, with velocity of up to 1.00–2.00m/s. The area of ponding in the south-east corner of the site reaches depths of 0.30–0.60m. The hazard rating for the majority of the flow is 'very low hazard'. The centre of the ponding is mostly classed as 'danger for some' with a smaller area of 'danger for most'.</p> <p>In the 0.1% AEP event, several significant surface water flow paths are present in the vicinity of the site- these are discussed further in 'Access and Egress', below.</p>
Reservoir	The site is not shown to be at risk of reservoir flooding from the available online maps.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence.</p> <p>The entire site is shown to have less than a 25% susceptibility to groundwater flood emergence. However, the JBA Groundwater Emergence Map shows that groundwater levels are between 0.025m and 0.5m below the ground across the entire site. This means that there is a risk of groundwater flooding to both surface and subsurface assets. There is the possibility of groundwater emerging at the surface locally. Any groundwater emerging at the site is likely to follow the topography flowing in a south-easterly direction away from the site.</p> <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p>
Sewers	The site is located in a postcode area (NR35 2) with 39 recorded historic sewer flooding, according to sewer flooding information provided by Anglian Water.
Flood history	<p>The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.</p> <p>Norfolk County Council's historic flooding records also do not show any flooding on or surrounding the site.</p>
Flood risk management infrastructure	
Defences	This site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	The site is not located in an Environment Agency Flood Alert or Flood Warning area.
Access and egress	<p>The site could be accessed via Church Road on the southern border or Norwich Road on the eastern border of the site.</p> <p>Whilst the western side of the site is not at significant risk from surface water, the eastern side of the site, along with Church Road to the south and Norwich Road to the east are likely to be impacted in the 3.3%, 1% and 0.1% AEP modelled surface water events. In the 0.1% event, surface water ponding in the southeast corner of the site could reach a maximum depth of 0.60m.</p> <p>The site, and surrounding roads, are unaffected by fluvial and coastal flooding according to the Environment Agency's Flood Map for Planning.</p> <p>Safe access and egress will need to be demonstrated in the 1% AEP plus climate change surface water event and fluvial events. Ideally, the access route should be situated 300mm above the designed flood level. Raising of access routes must not impact on surface water flow routes.</p> <p>Consideration should be given to the siting of access points with respect to areas of flood risk.</p>

<p>Dry Islands</p>	<p>The site is not located on a dry island.</p>
<p>Climate change</p>	
<p>Implications for the site</p>	<ul style="list-style-type: none"> • Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding. • The site is not at risk of fluvial flooding in the present day or future scenario. • Climate change should also be considered for surface water events; at the site-specific stage, the 1% AEP +40% event is considered as part of surface water drainage strategies, or surface water modelling. The 1% AEP +40% Climate Change upper uplift (for the Broadland Rivers Management Catchment peak flows) event mapping suggests that the site is likely to be at a slight increased risk of surface water flooding in future, with the area of ponding in the south-east corner of the site increasing in diameter by approximately 10m. Risk to the Church Road and Norwich Road also increases slightly in this climate change scenario. • Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
<p>Requirements for drainage control and impact mitigation</p>	
<p>Broad-scale assessment of possible SuDS</p>	<p>Geology & Soils</p> <ul style="list-style-type: none"> • Geology at the site consists of: • Bedrock- Neogene to Quaternary Rocks (undifferentiated)- Gravel, Sand, Silt and Clay • Superficial- Till-Diamicton • Soils at the site consist of: • Slightly acid loamy and clayey soils with impeded drainage <p>SuDS</p> <ul style="list-style-type: none"> • The site is considered to have a low susceptibility to groundwater. Detention and attenuation features should be designed to prevent groundwater ingress from impacting hydraulic capacity and structural integrity. Groundwater monitoring is recommended to determine the seasonal variability of groundwater levels, as this may affect the design of the surface water drainage system. Below ground development such as basements may not be appropriate at this site. • BGS data indicates that the underlying geology are conglomerates, gravel, silt, sand and muds which are likely to be with highly variable permeability. This should be confirmed through infiltration testing. Off-site discharge in accordance with the SuDS hierarchy may be required to discharge surface water runoff from the site. • The site is not located within a historic landfill site. • The entire site is located within a Groundwater Source Protection Zone 3. Infiltration techniques may not be suitable and should only be used following the granting of any required environmental permits from the Environment Agency for Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints. • Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. It may be possible to reduce site runoff by maximising the permeable surfaces on site using a combination of permeable surfacing and soft landscaping techniques. • The Risk of Flooding from Surface Water (RoFSW) mapping indicates the presence of surface water flow paths during the 0.1% AEP event. Existing flow paths should be retained and integrated with blue-green infrastructure and public open space. • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.

<p>Opportunities for wider sustainability benefits and integrated flood risk management</p>	<ul style="list-style-type: none"> • Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development. • Opportunities to incorporate source control techniques such as green roofs, blue/green corridors, permeable surfaces and rainwater harvesting must be considered in the design of the site.
--	--

NPPF and planning implications

<p>Exception Test requirements</p>	<ul style="list-style-type: none"> • The Local Authority will need to confirm that the sequential test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied. The NPPF classifies residential development as 'More Vulnerable'. • As the site contains an area at risk of surface water flooding, the Exception Test needs to be applied. • The Exception Test will be passed if the area at risk of surface water flooding in the southeast corner of the site is left undeveloped and instead incorporated as amenity greenspace.
---	--

<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site is more than 1 hectare in area and there is a risk of surface water flooding. • All sources of flooding, particularly the risk of fluvial and surface water should be considered as part of a site-specific flood risk assessment. • The site-specific FRA should be carried out in line with the National Planning Policy Framework, Flood Risk and Coastal Change Planning Practice Guidance, South Norfolk Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document. • Consultation with the Local Authority, Lead Local Flood Authority, Water Company, and the Environment Agency should be undertaken at an early stage. <p>Guidance for site design and making development safe:</p> <ul style="list-style-type: none"> • Safe access and egress will need to be demonstrated in the 1% AEP plus climate change fluvial and rainfall events, using the depth, velocity and hazard outputs. Ideally, the access route should be situated 300mm above the designed flood level. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk. • The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates. • Areas at risk from surface water flooding should ideally be integrated into green infrastructure, which presents wider opportunities to improve biodiversity and amenity as well as climate change adaptation. Integrated flood risk management and sustainable drainage scheme for the site is advised. It is essential that a detailed model of surface water flooding, using the existing drainage system, topographical and asset survey is constructed at the FRA stage. This will determine the risk from surface water flooding further and help to ensure that overland flows do not overwhelm future sustainable drainage features. • The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA, IDB or Anglian Water).
---	---

Key messages

The development is likely to be able to proceed if:

- Safe access and egress can be demonstrated in the 1% AEP plus climate change surface water event.
- A site-specific FRA demonstrates that the site is not at an increased risk of surface water flooding in the future, that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties, and how the natural flood storage provided by the pre-developed site is preserved.

Mapping Information

The key datasets used to make planning recommendations regarding this site were the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	For fluvial flood risk, climate change data was not available for this site. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	The site is not shown to be at significant risk of flooding from fluvial sources.
Surface Water	The Environment Agency's Risk of Flooding from Surface Water dataset has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, velocity, and hazard mapping is taken Environment Agency's Risk of Flooding from Surface Water mapping.



South Norfolk Council Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details

Site Code	VCDIT1
Address	Land between Thwaite Rd/Tunneys Lane, Ditchingham, South Norfolk, 634229 291610
Area	1.8ha
Current land use	Greenfield
Proposed land use	Residential
Internal Drainage District (IDD)	Adjacent to the Waveney, Lower Yare and Lothingland IDD

Sources of flood risk

Location of the site within the catchment	The site is located in the Broome Beck Catchment, north of Ditchingham. The Broome Beck flows from its source in Bedingham, east, past Ditchingham, and joins the River Waveney at Broome.
Existing drainage features	Local topography shows that the site slopes gently downhill towards the northeast, which suggests existing drainage is towards Broome Beck which is approximately 350m to the northeast of the site.
Fluvial	<p>The proportion of site at risk (Environment Agency's Flood Map for Planning Flood Zones): FZ3b – 0% FZ3a – 0% FZ2 – 1% FZ1 – 99%</p> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%).</i></p> <p>Available data: The Environment Agency's (EA) Flood Map for Planning has been used within this assessment.</p> <p>Flood characteristics: The EA's Flood Map for Planning shows a very small area of the site on the northern boundary is located within Flood Zone 2. The site is not located in Flood Zone 3a or 3b.</p>
Coastal and Tidal	The site is not at risk from tidal or coastal flooding.
Surface Water	<p>Proportion of site at risk (RoFSW): 3.3% AEP – 1% Max depth – 0.15 – 0.30m Max velocity – 0.01 – 0.25m/s 1% AEP – 2% Max depth – 0.30 – 0.60m Max velocity – 0.25 – 0.50m/s</p>

	<p>0.1% AEP – 5% Max depth – 0.30 – 0.60m Max velocity – 0.50 – 1.00m/s</p> <p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a greater Annual Exceedance Probability (AEP) (e.g. 1% AEP % includes the 3.3% AEP %).</i></p> <p>Description of surface water flow paths: In the 0.1% AEP event, there are small areas of surface water ponding to a maximum depth of 0.6m, and hazard rating of 'danger for some', in a low topographic spot on the northern boundary of the site and on the eastern boundary where the site meets Waveney Road and on the southern boundary of the site. During the 1% AEP, the extents of these areas decrease, and during the 3.3% AEP, only a marginal part of the site is impacted, with the maximum depth decreasing to 0.3m and the hazard rating decreasing to 'very low hazard'.</p>
Reservoir	The site is not shown to be at risk of reservoir flooding from the available online maps.
Groundwater	<p>The Environment Agency Areas Susceptible to Groundwater Flooding, provided as 1km grid squares, shows the susceptibility of an area to groundwater flood emergence. The following comments can be made about groundwater flood risk:</p> <ul style="list-style-type: none"> The entire site has a $\geq 75\%$ susceptibility to groundwater flood emergence. <p>The assessment does not negate the requirement that an appropriate assessment of the groundwater regime should be carried out at the site-specific FRA stage.</p> <p>The JBA Groundwater Emergence Map indicates predicted groundwater levels are within 0.5m and 5m of the ground surface at the site location, meaning surface manifestation is unlikely, although there is a risk of flooding to subsurface assets at the site. The 0.1% AEP surface water flood extents highlight the potential for groundwater emerging to the north and south of the site to impact access to and egress from the site.</p>
Sewers	The site is located in a postcode area (NR35 2) with 42 recorded historic sewer flooding incidences between May 2013 and March 2024, according to information provided by Anglian Water.
Flood history	<p>The Environment Agency's historic flooding and recorded flood outlines datasets do not have a record of any flooding on or surrounding the site.</p> <p>Norfolk County Council's historic flooding records also do not show any flooding on or surrounding the site.</p>
Flood risk management infrastructure	
Defences	This site is not protected by any formal flood defences.
Residual risk	There is no residual risk to the site from flood risk management structures.
Emergency planning	
Flood warning	A very small area of the site on the northern boundary is within the River Waveney from Diss and the River Dove to Ellingham, including Bungay Flood Alert Area. The site is not located in a Flood Warning area.
Access and egress	<p>The site can currently be accessed by vehicles off Thwaite Road to the west.</p> <p>In all modelled fluvial events, the site and surrounding roads are unaffected by flooding.</p> <p>During the 3.3% and 1% AEP surface water events, flooding is not predicted to impact Thwaite Road. During the 0.1% AEP, an area of surface water ponding may extend from the field to the west of the site onto Thwaite Road. Depths could reach up to 0.6m on the road to a maximum velocity of 1.25m/s and maximum hazard rating of 'danger for some', meaning access and egress for emergency vehicles may be affected.</p> <p>Safe access and egress will need to be demonstrated in the 1% AEP plus climate change surface water event. Site drainage proposals should address the requirements for access routes, avoid impeding surface water flows and preserve the storage of surface water to avoid exacerbation of flood risk in the wider catchment.</p>

<p>Dry Islands</p>	<p>The site is not located on a dry island.</p>
<p>Climate change</p>	
<p>Implications for the site</p>	<ul style="list-style-type: none"> • Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding. • In the absence of detailed modelling, Flood Map for Planning Flood Zone 2 can be used as an indicative 1% + climate change flood extent. This suggests the site may be at greater fluvial flood risk in the future as Flood Zone 2 extends approximately 100m more towards the site than Flood Zone 3. • Climate change should also be considered for surface water events; at the site-specific stage, the 1% AEP +40% event is considered as part of surface water drainage strategies, or surface water modelling in the Broadland Rivers Management Catchment for the 2070s. The 1% AEP +40% event mapping suggests that the site is not likely to be at significantly increased risk of surface water flooding in future. • Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
<p>Requirements for drainage control and impact mitigation</p>	
<p>Broad-scale assessment of possible SuDS</p>	<p>Geology & Soils</p> <ul style="list-style-type: none"> • Geology at the site consists of: <ul style="list-style-type: none"> ◦ Bedrock- Gravel, sand, silt and clay ◦ Superficial- Sand and gravel, river terrace deposits • Soils at the site consist of: <ul style="list-style-type: none"> ◦ Freely draining slightly acid sandy soils <p>SuDS</p> <ul style="list-style-type: none"> • The site is considered to be highly susceptible to groundwater flooding. Groundwater flooding could occur at the surface which may flow to and pool within topographic low spots during very wet winters. Detention and attenuation features should be designed to prevent groundwater ingress from impacting hydraulic capacity and structural integrity. Additional site investigation work may be required to support the detailed design of the drainage system. This may include groundwater monitoring to demonstrate that a sufficient unsaturated zone has been provided above the highest occurring groundwater level. Below ground development such as basements are not appropriate at this site. • BGS data indicates that the underlying geology is sands, gravels, silts and clays which is likely to be free draining. This should be confirmed through infiltration testing, with the use of infiltration maximised as much as possible in accordance with the SuDS hierarchy. This would suggest a lower groundwater flood risk than is indicated by the EA's Areas Susceptible to Groundwater Flooding (AStGWF) map. The AStGWF is a strategic-scale map and only isolated locations within the overall susceptible area are actually likely to suffer the consequences of groundwater flooding, therefore the map should be treated as indicative. • The site is located within a Groundwater Source Protection Zone. Infiltration techniques may not be suitable and should only be used following the granting of any required environmental permits from the Environment Agency for Source Protection Zones 2, 3 and 4 although it is possible that infiltration may not be permitted. Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints. • The site is not located within a historic landfill site. • Surface water discharge rates should not exceed the existing greenfield runoff rates for the site. Opportunities to further reduce discharge rates should be considered and agreed with the LLFA. • If it is proposed to discharge runoff to a watercourse or sewer system, the condition and capacity of the receiving watercourse or asset should be confirmed through surveys and the discharge rate agreed with the asset owner.

Opportunities for wider sustainability benefits and integrated flood risk management

- Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints.
- Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development
- Opportunities to incorporate infiltration techniques such as filter strips, filter drains and bioretention areas must be considered. Consideration should be made to the existing condition of receiving waterbodies and their Water Framework Directive objectives for water quality. The use of multistage SuDS treatment will clean improve water quality of surface water runoff discharged from the site and reduce the impact on receiving water bodies.
- Opportunities to incorporate source control techniques such as green roofs, permeable surfaces and rainwater harvesting must be considered in the design of the site.
- The potential to utilise conveyance features such as swales to intercept and convey surface water runoff should be considered. Conveyance features should be located on common land or public open space to facilitate ease of access. Where slopes are >5%, features should follow contours or utilise check dams to slow flows.

NPPF and planning implications

Exception Test requirements

- The Local Authority will need to confirm that the Sequential Test has been carried out. The Sequential Test will need to be passed before the Exception Test is applied. The NPPF classifies residential development as 'More Vulnerable'.
- As the site is at risk of groundwater flooding and surface water flooding, as well as fluvial flooding in the future, the Exception Test needs to be applied. The Exception Test will be passed if the area at risk of surface water flooding in the northern part of the site is left undeveloped and instead incorporated as amenity greenspace.

Requirements and guidance for site-specific Flood Risk Assessment

Flood Risk Assessment:

- At the planning application stage, a site-specific Flood Risk Assessment will be required as the proposed development site contains a small area at fluvial and surface water flood risk, is indicated to be at significant groundwater flood risk and is more than 1 hectare in area.
- All sources of flooding should be considered as part of a site-specific flood risk assessment.
- The site-specific FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance, Norwich City Council's Local Plan policies, and the Norfolk County Council Lead Local Flood Authority's Statutory Consultee for Planning Guidance Document.
- Consultation with the Local Authority, Lead Local Flood Authority, Water Company, and the Environment Agency should be undertaken at an early stage.
- The development should be designed to ensure that mitigation measures are in place to ensure the development does not flood.

Guidance for site design and making development safe:

- Safe access and egress will need to be demonstrated in the 1 % AEP plus climate change rainfall event, using the depth, velocity and hazard outputs. Raising of access routes must not impact on surface water flow routes or contribute to loss of floodplain storage. Consideration should be given to the siting of access points with respect to areas of surface water flood risk
- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond current greenfield rates.

	<ul style="list-style-type: none"> The proposed site should discharge surface water at the original pre-development (greenfield) runoff rate. If this is not possible, a significant reduction in the current rate of discharge should be achieved and agreed with the relevant drainage body (LLFA, IDB or Anglian Water). Developers should refer to Norfolk County Council's 'Norfolk County Council Lead Local Flood Authority Statutory Consultee for Planning Guidance Document' and the Level 1 SFRA for information on SuDS for guidance on the information required by the LLFA from applicants to enable it to provide responses to planning applications.
--	--

Key messages

The development is likely to be able to proceed if:

- Safe access and egress can be demonstrated in the 1% AEP plus climate change surface water event. The current access point on Thwaite Road is likely to be unaffected by surface water flooding in the 1% AEP event but may be affected in the 0.1% AEP event.
- A site-specific FRA demonstrates that the site is not at an increased risk of flooding in the future, that the development of the site does not increase the risk of surface water flooding on the site and to neighbouring properties, and how the natural flood storage provided by the pre-developed site is preserved.
- If flood mitigation measures are implemented then they are tested to ensure that they will not displace water elsewhere (for example, if land is raised to permit development on one area, compensatory flood storage will be required in another).

Mapping Information

The key datasets used to make planning recommendations regarding this site were the Environment Agency's Flood Map for Planning and the Risk of Flooding from Surface Water map. More details regarding data used for this assessment can be found below.

Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.
Climate change	In the absence of detailed modelling, the Environment Agency's Flood Map for Planning Flood Zone 2 has been used as an indication of flood extent during a 1% + climate change scenario. For surface water risk, a 1% AEP +40% scenario has been considered, which represents the Broadland Rivers Management Catchment for the 2070s.
Fluvial depth, velocity and hazard mapping	This site is not shown to be at significant risk of flooding from fluvial sources.
Surface Water	The Risk of Flooding from Surface Water dataset has been used to define areas at risk from surface water flooding.
Surface water depth, velocity and hazard mapping	The surface water depth, velocity, and hazard mapping is taken Environment Agency's Risk of Flooding from Surface Water mapping.